

Fork Slot Truss Jibs

Fork Slot Truss Jibs - Attachments jibs could be used on industrial lift trucks, extendable-reach forklifts, and on rough terrain straight-mast lift trucks. The forklift jib cranes could be installed onto the forklift by way of inserting both of the forks into the fork pockets. The rear of the jib crane then seats against the back of the fork and a security chain wraps the forklift carriage to hold it into place.

Load Capacity for the Jib Boom Forklift Attachment

The load capacity of a forklift jib has a most of about 1935 lbs up to 6000 pounds on either the extended or retracted positions range. You might have to discuss with a material handling specialist about the particular limits of your lift truck application. The load capacity rankings are intended for the jib itself and not the forklift or the maximum load which can be lifted safely making use of a particular forklift. It is very important keep in mind that each time whichever attachments like for example a lift truck jib are fitted to the lift truck, the new center of gravity made by the attachment would lessen the overall lift capability of the forklift. There are directions obtainable which offer details on how to properly determine these load limits.

Before utilizing any forklift jib, be sure that the shackles and hooks are properly secured to the forklift. Be sure and even double check that the pins are tight. It is very important that the load calculations are correctly done and double checked. Remember to take into account the fact that rated capacities sometimes lessen whenever the boom is in a raised position, when the boom is extended with telehandlers or whenever the mast is tilted forward.